WAGONS SINCE 1960



Farm Wagon



This version of our quick-hitch latch and front clevis is used on all models and sizes.



Horst exclusive bearings on king pin and center pivot for absolute no sway trailing - standard on all models.




We use Horst exclusive bearings on all steering pivots.





Farm Wagon

10 Ton



• It eliminates the problem of bent reaches. All models have Taper Roller Bearing Tongue Mount and greasable automotive style ball joints.

Shown with 11L x 15" HS Tires 76" Track width Ideal for Forage Box and other applications

12 Ton




Shown with 12 x 22.5" Used Truck Tires 82" Track width

 This heavy duty model incorporates the same basic design and features as the model 185 but has bigger axles, hubs and wheels. Model 205

Farm Wagon

Same Model as left Shown with 12.5L x 15' HS Floatation Tires 82" Track width





Bearings standard in tongue pivot on all models.





Model 865 QuadSteer

Heavy Duty 8-Wheel Wagon

16 TON - THE TRUE POWER OF 4X4

Horst wagons welcomes you to a new generation of running gear. Designed for smoother travel and minimal soil compaction, the new 865 QuadSteer is changing the way you move from the field to the farm.

With the addition of a dual front axle set, the new 865 combines two advantages into one: improved floatation and easier steering. Unlike any other running gear, the 865's second steering axle provides better weight distribution at the front of the wagon - especially while turning, when soil compaction happens most.

The double front axle also provides a smoother ride which reduces unnecessary wear and tear on your equipment and avoids damaging the load.

Built to carry up to 16 tons, the 865 is mount ready for any type of deck.

Road travel is made easier with reduced trailer sway from Horst's proven tapered roller bearings which respond instantly to minor movements, keeping your wagon in line.

No matter what you mount on top, you can always rely on the strength and stability of the new 865 QuadSteer. Talk to your authorized Horst Wagons dealer today.

Optional Features

All Models



Shown here is optional spring balancer for ease and convenience of hook-up.



3/8" GR. 70 plated transport chain meets current D.O.T. standards.





Factory installed hydraulic disc or drum surge brakes for added control and safety.



Tandem







Specifications

for Wagons and Optional Features

	4 WHEEL MODELS				6 WHEEL MODELS			8 WHEEL
MODEL	145	185	205	275	245	265	325	865
CAPACITY	16,000 LB	20,000 LB	24,000 LB	28,000 LB	24,000 LB	28,000 LB	32,000 LB	32,000 LB
TRACK WIDTH 15 x 6 x 6 15 x 8 x 6 15 x 10 x 6 16 x 6 x 6 16 x 8 x 6 15 x 10 x 8 22.5 x 8.25 x 8 22.5 x 11.25 x 8	74" 74" 75" 74" 74" N/A N/A N/A	76" 76" 77" 76" 76" N/A N/A N/A	N/A N/A N/A N/A N/A 82" 82" 82"	N/A N/A N/A N/A N/A N/A N/A 89"	76" 76" 77" 76" 76" N/A N/A N/A	N/A N/A N/A N/A N/A 82" 82" N/A	N/A N/A N/A N/A N/A N/A N/A 89"	N/A N/A N/A N/A N/A 82" 82" 82"
SPINDLES	1-3/4" DIA. C1045 HOT ROLLED	2" DIA. C1045 HOT ROLLED	2-1/4" DIA. C1045 COLD ROLLED	2-3/4" DIA. C1045 COLD ROLLED	FRONT 2-3/4" DIA. C1045 COLD ROLLED REAR 2-1/4" DIA. C1045 COLD ROLLED	2-1/4" DIA. C1045 COLD ROLLED	2-3/4" DIA. C1045 COLD ROLLED	2-1/4" DIA. C1045 COLD ROLLED
HUBS	6 BOLT 4000 LB.	6 BOLT 6000 LB.	8 BOLT 6500 LB.	8 BOLT 8000 LB.	6 BOLT 6000 LB.	8 BOLT 6500 LB.	8 BOLT 8000 LB.	8 BOLT 6500 LB.
BEARINGS - Bore Size (Inner / Outer)	TAPER ROLLER 1.50 / 1.25	TAPER ROLLER 1.80 / 1.38	TAPER ROLLER 1.80 / 1.38	TAPER ROLLER 2.165 / 1.625	TAPER ROLLER 1.80 / 1.38	TAPER ROLLER 1.80 / 1.38	TAPER ROLLER 2.165 / 1.625	TAPER ROLLER 1.80 / 1.38
FRONT AXLE	5 1/2 x 3 x .188 WALL	6 x 3 x .250 WALL	7 x 3 x .250 WALL	8 x 3 x .250 WALL	6 x 3 x .210 WALL	7 x 3 x .250 WALL	8 x 3 x .250 WALL	7 x 3 x .250 WALL
REAR AXLE	5 1/2 x 3 x .188 WALL	6 x 3 x .250 WALL	7 x 3 x .250 WALL	8 x 3 x .250 WALL	6 x 3 x .250 WALL	7 x 3 x .313 WALL	8 x 3 x .250 WALL	7 x 3 x .313 WALL
TONGUE BRACKET MOUNTING	1-1/2" BOLT BEARING MTD.							
TONGUE BOLT	7/8" DIAMETER 1-1/8" DIAMETER							
TONGUE LATCH	RETRACTABLE AUTOMATIC RELOCK - STANDARD ON ALL MODELS							
REACH POLES	3" O.D. x .188 WALL - ROUND TUBE							
BOLSTER STAKES	ADJUSTABLE 30" - 40" - 42"							
STEERING	AUTOMOTIVE TYPE							
TIE ROD ENDS	GREASABLE AUTOMOTIVE STYLE BALL JOINTS							
WHEEL BASE	ADJUSTABLE							
HEIGHT FROM GROUND TO TOP OF BUNK	23" ON 9.5 x 15 TIRES	24" ON 11L x 15 TIRES	26" (12.5 X 16 TIRES) 30" (11 X 22.5 TIRES)	30" ON 11 x 22.5 TIRES	23" ON 11L x 15 TIRES	26" (12.5 X 16 TIRES) 30" (11 X 22.5 TIRES)	30" ON 11 x 22.5 TIRES	26" (12.5 X 16 TIRES) 30" (11 X 22.5 TIRES)
APPROX. WEIGHT	610 LB.	750 LB.	1010 LB.	1120 LB.	1050 LB.	1290 LB.	1450 LB.	1720 LB.
2 WHEEL HYD. DRUM SURGE BRAKES	OPTIONAL	N/A	OPTIONAL	OPTIONAL	N/A	OPTIONAL	OPTIONAL	OPTIONAL
4 WHEEL HYD. DRUM SURGE BRAKES	N/A	N/A	N/A	OPTIONAL	N/A	OPTIONAL	OPTIONAL	OPTIONAL
2 WHEEL HYD. DISC BRAKES	N/A	N/A	N/A	OPTIONAL	N/A	N/A	OPTIONAL	N/A
SAFETY CHAIN (optional)	3/8" GR. 70							
SPRING BALANCER KIT	OPTIONAL							
SPRING CUSHION TONGUE	OPTIONAL (NOT AVAILABLE WITH BRAKES)							
ROCKING BOLSTER	OPTIONAL							

HORST WELDING • 8082 Road 129, RR 3, Listowel, Ontario N4W 3G8 Canada

PHONE: 519-291-4162 **TOLL FREE:** 866-567-4162

FAX: 519-291-5388 EMAIL: sales@horstwelding.com WEBSITE: www.horstwelding.com



